



WIRELINER PRESSURE CONTROL EQUIPMENT

PRODUCT FEATURES

- H2S or Standard Service
- 5,000 to 15,000 PSI Cold Working Pressure
- Standard Quick Union Connections
- Standard Nominal Sizes – 3" to 7"
- Complete with Thread Protectors, Material Certification and Hydrostatic Pressure Test
- **Custom Sizes and Configurations Available**

GKD STUFFING BOX

- Slickline 0.066" to 0.125"
- 16" High Capacity Aluminium or Composite Sheave Standard
- Maximum Working Load 6,000 lbs. (3,000 lbs. line)
- Hydraulic or Manual Activation

GKD LUBRICATOR RISERS

- Available with optional 1/2" Bleed/Pump-in Ports and Stainless Steel Valves
- 8' Standard Length – Custom lengths available

GKD WIRELINER BLOWOUT PREVENTERS

- Hydraulic or Manual Activation
- Single or Twin
- Integrated low-profile equalizer
- Standard with Quick Union Connections

RELATED PRODUCTS

- GKD Hay Pulley – Standard 16" Sheave
- GKD Hydraulic Hand Pump – Models for BOP and Stuffing Box
- Chemical Injection Sub
- Crossover Adapters
- Lubricator Lifting Clamps
- Pick-up Sub, Ported Night Cap
- Pump-in Sub
- Wellhead Adapters – Swedge Adapters and Flange Adapters, Internal Pick-up Threads available

